Type:

CLA SERIES LED AREA

DIMENSIONS

Dimensions shown for 8L - 20L Brick Unit



Dimensions shown for 25L - 40L Brick Unit



Dimensions shown for 45L - 60L Brick Unit



WLS LIGHTING SYSTEMS
1919 Windsor Place
Fort Worth, TX 76110
800.633.8711
www.wlslighting.com

SPECIFICATIONS

APPLICATION - The CLA Series of high output LED luminaries are designed to be a replacement for HID area lights. It is optimal for lighting applications where long life, low maintenance and consistent color rendering are required. Areas with limited accessibility due to fixture location or where heavy pedestrian or vehicle traffic makes maintenance difficult are ideal applications. The high wattage/lumen output allows the fixture to be used for parking, restaurant, quick service, shopping centers or general area lighting applications.

CONSTRUCTION - The heavy-duty housing is constructed of cast aluminum with heat dissipating fins. The optical assemblies are sealed in place using a silicone gasket for weather tight protection. Modular LED system for ease of maintenance. ETL listed for wet locations (IP65). Each fixture can accommodate advanced wireless control, management and reporting systems for outdoor lighting when ordered with the CLAARM mounting (required).

FINISH - A corrosion-resistant epoxy E-Coat layer that forms a uniform and all-encompassing protective barrier is applied to the the fixture prior to electrostatically applying a super durable powder coat finish. Standard colors available: Black, Bronze, US Green and White. Custom colors available upon request.

OPTICAL SYSTEM - Made with state of the art UV stabilized acrylic high performance refractive optical assemblies that use high transmissivity materials to achieve precise photometric distributions. Available in Type II, III, IV, IV Automotive, Automotive Frontline Wide, IV Tennis, V Medium and V Wide Beam configurations. Optics may be ordered rotated 90 degrees for perimeter lighting or walkway applications (optics are not field rotatable). Star Light friendly (meets or exceeds Dark Sky requirements) in the horizontal position.

ELECTRICAL SYSTEM - Available in up to a 60,000 lumens output LED system in 5000K Cool White (+/- 500K) or 4000K Neutral White color temperature. Available with 120-277 50/60 Hz power supply. LED's rated for over 50,000 hours at 25°C ambient temperature. 480V and 347V input option available, 0-10V dimming. Built-in surge protection up to 10 kV. Built-In Active PFC Function >95% Full load. LED Power Supply conforms to UL8750 standards.

MOUNTING - Proprietary slide-on mounting system allows for quick installation. The CLA can be ordered with an aesthetically pleasing arm mount (CLAARM - required for integrated dynamic control systems), a 2" adjustable slip fitter (CLA2AF) for mounting on a standard 2-3/8" OD tenon and an entire compliment of pole brackets with integrated quick mount technology. CLASAM for direct mounting to poles in single (180°) or D180 (2@ 180°).

LISTINGS - Complies with UL8750, ETL listed for damp locations. Meets US and Canadian safety standards. -40°C to 50°C ambient operation, RoHS Compliant.

FIXTURE WEIGHTS (APPROXIMATE)			
	2 BRICK	4 BRICK	6 BRICK
Weight (lbs)	14 lbs	20 lbs	28 lbs

Project Name: _____
Date: _____
Location: _____
Notes: _____

55 REV. 08/20
Specifications subject to change without notice.

CLA SERIES LED AREA

ORDERING INFORMATION SELECT APPROPRIATE CHOICE FROM EACH COLUMN TO FORMULATE ORDER CODE.
Refer to example below.

PRODUCT	COLOR TEMP	NOMINAL LUMENS	OPTICS	VOLTAGE	OPTIONS	FINISH	ACCESSORIES
CLA	**C** Cool White (5000K) **N** Neutral White (4000K) **W** Warm White (3000K)[2]	**8L** 8000 Lumens [1] **12L** 12,000 Lumens [1] **15L** 15,000 Lumens [1] **20L** 20,000 Lumens **25L** 25,000 Lumens [1] **30L** 30,000 Lumens [1] **33L** 33,000 Lumens **40L** 40,000 Lumens **45L** 45,000 Lumens [1] **50L** 50,000 Lumens **55L** 55,000 Lumens **60L** 60,000 Lumens	**T2** Type II **T3** Type III **T4** Type IV **FAW** Frontline Auto Wide **T4T** Type IV Tennis **T5M** Type V Medium **T5W** Type V Wide	**1** Multi-Volt [3] **2** 347-480 (MV)	**PCR7** 7-Pin Twist-Lock Photocell Receptacle ANSI C136.41 & Receptacle Shorting Cap [4]	**BZ** Bronze **BK** Black **GR** US Green **WH** White **SP** Special [5]	**CLA2AF** 2" Adjustable Slip Fitter [6] **PC2** 480V Twist-Lock Photocell **PC7** Multi-Tap (105-285V) Twist-Lock Photocell **CLAARM** Decorative Arm Mount (0.3 EPA, 3.7 lbs) [7] **CLASM** Slide Mount Adapter [6,7] **CLAARMR** Decorative Arm Mount for Round Poles (0.3 EPA, 3.7 lbs) **CLAARMPSP** Arm with Integrated PIR Motion Sensor **S215** Angled Back Light Shield [1] **TLWFSIR-L1** 360° Lens, Maximum Coverage 40' Diameter From 16' Height **TLWFSIR-L2** 360° Lens, Maximum Coverage 48' Diameter From 8' Height **TLWFSIR-L3** 360° Lens, Maximum Coverage 60' Diameter From 20' Height **TLWFSIR-L4** 360° Lens, Maximum Coverage 60' Diameter From 40' Height **TLWFSIR-L7** 360° Lens, Maximum Coverage 100' Diameter From 40' Height **CLAHT23B** Horizontal 2-3/8" OD Tenon Mount
ORDER:							
WLS-CLA							

Example: WLS-CLA-N-25L-T5W-1-B-PCR7-BZ

FOOTNOTES:
1. Multi-Volt is an auto ranging power supply from 100V to 320C input.
2. Cool White (5000K) and Warm White (3000K) are optional for additional information.
3. Slide mount adapter for direct pole mounts cannot be used when mounting fixtures at 90° increments.
4. Order one for 8L-20L units, two for 25L-40L units, three for 45L-60L units.
5. Accessory mounting device must be ordered for each luminaire to provide mounting means.
6. PCR7 photocell receptacle must be oriented in the field so that the light sensor on the control is facing North. Failure to orient the CLA with the factory default position will void warranty.
7. 8L, 10L, 12L, 15L, 25L, 30L and 45L are the only Nominal Lumen Packages available in a Warm White color temperature. All other lumen packages are only available in Cool White or Neutral White.

CLAARM Decorative Arm Mount (0.3 EPA, 3.3 lbs) with Slide Mount Adapter

CLA2AF 2" Adjustable Slip Fitter with Slide Mount Adapter

CLASM Slide Mount Adapter

PC2 480V Twist-Lock Photocell

PC5 Multi-Tap (105-285V) Twist-Lock Photocell

PCR7 7-Pin Twist-Lock Photocell Receptacle ANSI C136.41 and Receptacle Shorting Cap

S215 Angled Back Light Shield

CLAHT23B Horizontal 2-3/8" OD Tenon Mount with Slide Mount Adaptor

NOTES
1 EPA is shown include both the fixture and the mounting apparatus.
2 CMSC10 Quick Mount only available for fixtures with up to 4 bricks.
3 Order one per LCD lock. Field installed.
4 PCR7 photocell receptacle must be oriented in the field so that the light sensor on the control is facing North.

LUMINAIRE EPA CHART - CLAARM			
FIXTURE CONFIGURATION	2 BRICK EPA's [1]	4 BRICK EPA's [1]	6 BRICK EPA's [1]
1 @ 90°	0.8	0.9	1.1
2 @ 180°	1.5	1.7	2.1
2 @ 90°	1.4	1.5	1.7
3 @ 90°	2.1	2.3	2.6
4 @ 90° or 4 @ 70°	2.2	2.5	2.6

WLS LIGHTING SYSTEMS
1919 Windsor Place
Fort Worth, TX 76110
800.633.8711
www.wlslighting.com

Project Name: _____
Date: _____
Location: _____
Notes: _____

55 REV. 08/20
Specifications subject to change without notice.

CLA SERIES LED AREA

IES INDOOR REPORT PHOTOMETRIC FILE NAME: CLAC60LT3

Type III Optical Assembly
60,000 Lumen, Cool White

465W CTL LED
Color Temperature: 5,000 K



IES INDOOR REPORT PHOTOMETRIC FILE NAME: CLAC60LT5M

Type V Medium Optical Assembly
60,000 Lumen, Cool White

465W CTL LED
Color Temperature: 5,000 K



WLS LIGHTING SYSTEMS
1919 Windsor Place
Fort Worth, TX 76110
800.633.8711
www.wlslighting.com

Project Name: _____
Date: _____
Location: _____
Notes: _____

55 REV. 08/20
Specifications subject to change without notice.

CLA SERIES LED AREA

COOL WHITE

Output ID	Nominal Lumens	Delivered Lumens							System Wattage	L70 @ 25° C	Amperage Draw				
		Type II	Type III	Type IV	Type 4T	FAW	Type 5M	Type 5W			120V	208V	240V	277V	347V	480V
8L	8,000	7934 B2 U0 G3	7678 B3 U0 G3	7105 B3 U0 G3	7591 B3 U0 G1	7060 B2 U0 G2	7850 B3 U0 G1	7264 B3 U0 G2	68	>50K	0.57	0.33	0.29	0.25	0.25	0.15
10L	10,000	9446 B3 U0 G3	10311 B3 U0 G3	9541 B3 U0 G3	10195 B3 U0 G2	9488 B3 U0 G2	10542 B3 U0 G1	9741 B3 U0 G2	93	>50K	0.78	0.45	0.39	0.34	0.27	0.20
12L	12,000	11321 B3 U0 G3	12030 B3 U0 G3	11132 B3 U0 G3	11895 B3 U0 G2	11070 B3 U0 G3	12330 B4 U0 G1	11366 B4 U0 G2	108	>50K	0.90	0.52	0.45	0.39	0.32	0.23
15L	15,000	13225 B3 U0 G3	14436 B3 U0 G3	13358 B3 U0 G3	14273 B3 U0 G2	13284 B3 U0 G3	14790 B4 U0 G1	13639 B4 U0 G2	135	>50K	1.13	0.65	0.57	0.49	0.39	0.29
20L	20,000	17194 B3 U0 G3	18767 B3 U0 G3	17367 B3 U0 G3	18556 B3 U0 G2	17271 B3 U0 G3	19180 B4 U0 G1	17731 B5 U0 G3	159	>50K	1.35	0.77	0.67	0.58	0.46	0.34
23L	23,000	22310 B3 U0 G3	24332 B3 U0 G4	22534 B4 U0 G4	24078 B4 U0 G2	22410 B3 U0 G3	24899 B5 U0 G1	23007 B5 U0 G3	220	>50K	1.84	1.06	0.92	0.80	0.64	0.46
30L	30,000	26455 B3 U0 G3	28870 B3 U0 G4	26715 B4 U0 G4	28545 B4 U0 G2	26568 B3 U0 G3	29519 B5 U0 G1	27276 B5 U0 G4	265	>50K	2.21	1.28	1.11	0.96	0.77	0.56
33L	33,000	31275 B3 U0 G3	34138 B3 U0 G4	31590 B4 U0 G4	33754 B4 U0 G2	31415 B3 U0 G3	34905 B5 U0 G1	32253 B5 U0 G4	294	>50K	2.45	1.42	1.23	1.07	0.85	0.62
40L	40,000	35918 B4 U0 G5	39206 B4 U0 G5	36279 B4 U0 G4	38765 B4 U0 G2	36079 B4 U0 G5	40087 B5 U0 G2	37041 B5 U0 G4	320	>50K	2.67	1.54	1.34	1.16	0.93	0.67
45L	45,000	40322 B4 U0 G5	43696 B4 U0 G5	40434 B5 U0 G5	43204 B5 U0 G3	40211 B4 U0 G5	44678 B5 U0 G2	41283 B5 U0 G5	400	>50K	3.34	1.93	1.67	1.45	1.16	0.84
50L	50,000	44809 B4 U0 G5	48473 B4 U0 G5	44855 B5 U0 G5	47928 B5 U0 G3	44607 B4 U0 G5	49563 B5 U0 G2	45757 B5 U0 G5	424	>50K	3.54	2.04	1.77	1.54	1.23	0.89
55L	55,000	49313 B4 U0 G5	53717 B5 U0 G5	49738 B5 U0 G5	53113 B5 U0 G3	49453 B4 U0 G5	54495 B5 U0 G2	50751 B5 U0 G5	455	>50K	3.80	2.19	1.90	1.65	1.32	0.95
60L	60,000	53878 B4 U0 G5	58830 B5 U0 G5	54419 B5 U0 G5	58167 B5 U0 G4	54118 B5 U0 G5	60131 B5 U0 G2	55582 B5 U0 G5	465	>50K	3.86	2.24	1.94	1.68	1.35	0.97

NEUTRAL WHITE

Output ID	Nominal Lumens	Delivered Lumens							System Wattage	L70 @ 25° C	Amperage Draw				
		Type II	Type III	Type IV	Type 4T	FAW	Type 5M	Type 5W			120V	208V	240V	277V	347V	480V
8L	8,000	6733 B2 U0 G3	7377 B3 U0 G3	6821 B3 U0 G3	7289 B3 U0 G1	6787 B2 U0 G2	7536 B3 U0 G1	6964 B3 U0 G2	68	>50K	0.57	0.33	0.29	0.25	0.20	0.15
10L	10,000	9096 B3 U0 G3	9959 B3 U0 G3	9160 B3 U0 G3	9785 B3 U0 G2	9125 B3 U0 G2	10121 B3 U0 G2	9352 B3 U0 G2	93	>50K	0.78	0.45	0.39	0.34	0.27	0.20
12L	12,000	10980 B3 U0 G3	11549 B3 U0 G3	10687 B3 U0 G3	11419 B3 U0 G2	10628 B3 U0 G3	11808 B4 U0 G1	10911 B4 U0 G2	108	>50K	0.90	0.52	0.45	0.39	0.32	0.23
15L	15,000	12897 B3 U0 G3	13869 B3 U0 G3	12824 B3 U0 G3	13703 B3 U0 G2	12758 B3 U0 G3	14170 B4 U0 G1	13094 B4 U0 G2	135	>50K	1.13	0.65	0.57	0.49	0.39	0.29
20L	20,000	16507 B3 U0 G3	18017 B3 U0 G3	16672 B3 U0 G3	17815 B3 U0 G2	16580 B3 U0 G3	18422 B4 U0 G1	17022 B5 U0 G2	159	>50K	1.33	0.77	0.67	0.58	0.46	0.34
23L	23,000	21418 B3 U0 G3	23379 B3 U0 G4	21634 B4 U0 G4	23116 B4 U0 G2	21514 B3 U0 G3	23906 B5 U0 G1	22098 B5 U0 G3	220	>50K	1.84	1.06	0.92	0.80	0.64	0.46
30L	30,000	25392 B3 U0 G3	27716 B3 U0 G4	25647 B4 U0 G4	27404 B4 U0 G2	25509 B3 U0 G3	28339 B5 U0 G1	26189 B5 U0 G4	265	>50K	2.21	1.28	1.11	0.96	0.77	0.56
33L	33,000	30025 B3 U0 G3	32722 B3 U0 G4	30326 B4 U0 G4	32404 B4 U0 G2	30159 B3 U0 G3	33509 B5 U0 G1	30963 B5 U0 G4	294	>50K	2.45	1.42	1.23	1.07	0.85	0.62
40L	40,000	34482 B4 U0 G5	37638 B4 U0 G5	34829 B4 U0 G4	37215 B4 U0 G2	34635 B4 U0 G5	38484 B5 U0 G2	35560 B5 U0 G4	320	>50K	2.67	1.54	1.34	1.16	0.93	0.67
45L	45,000	38811 B4 U0 G5	41948 B4 U0 G5	38817 B5 U0 G5	41476 B5 U0 G3	38602 B4 U0 G5	42891 B5 U0 G2	39622 B5 U0 G5	400	>50K	3.34	1.93	1.67	1.45	1.16	0.84
50L	50,000	42653 B4 U0 G5	46535 B4 U0 G5	43061 B5 U0 G5	46011 B5 U0 G3	42823 B4 U0 G5	47581 B5 U0 G2	43965 B5 U0 G5	424	>50K	3.54	2.04	1.77	1.54	1.23	0.89
55L	55,000	47261 B4 U0 G5	51568 B5 U0 G5	47719 B5 U0 G5	50988 B5 U0 G3	47436 B4 U0 G5	52728 B5 U0 G2	48721 B5 U0 G5	455	>50K	3.80	2.19	1.90	1.65	1.32	0.95
60L	60,000	51723 B4 U0 G5	56457 B5 U0 G5	52283 B5 U0 G5	55822 B5 U0 G4	51954 B5 U0 G5	57728 B5 U0 G2	53339 B5 U0 G5	465	>50K	3.86	2.24	1.94	1.68	1.35	0.97

WLS LIGHTING SYSTEMS
1919 Windsor Place
Fort Worth, TX 76110
800.633.8711
www.wlslighting.com

Project Name: _____
Date: _____
Location: _____
Notes: _____

55 REV. 08/20
Specifications subject to change without notice.

McADAMS
The John R. McAdams Company, Inc.
2905 Meridian Parkway
Durham, NC 27713

phone 919. 361. 5000
fax 919. 361. 2269
GA license number: PEF007872

www.mcadamsco.com

CLIENT

N3 REAL ESTATE
1240 N KIMBALL AVE
SOUTHLAKE, TX
PHONE: 817.348.8748

N3 REAL ESTATE®

STRICKLAND BROTHERS OIL CHANGE - DAWSONVILLE

SITE PLAN SUBMITTAL
HIGHWAY 53, NORTHWEST OF ITS INTERSECTION WITH CENTER LANE
DAWSONVILLE, GA 30534

NCT SERIES LED WALL

Type:

3L - 7L

DIMENSIONS



SPECIFICATIONS

CONSTRUCTION & MATERIALS
- Luminaire housing is rugged die cast aluminum with integral LED driver compartment is specifically designed for LED applications with advanced LED thermal management and driver
- Luminaire mounting box designed for easy installation of a variety of junction box styles: 4" square, 3" and 4" octagonal, single-gang, vertical or horizontal mounts
- Luminaire can also be direct mounted to a wall and surface wired
- Direct mount to junction box with knockouts and grommet on back
- 11L, 17L and 23L housings have knockouts for additional mounting screws to provide added mounting stability (recommended)
- Luminaires (1L and 3L) allow for through wired or conduit entry from the top, sides and rear
- Luminaires (7L and higher) allow for through-wired or conduit entry from the top, bottom, sides and rear
- Housing includes a knockout for field installed button type photocontrol (by others)
- Housing and mounting accessories finished in polyester powder coat paint, 2.5 mil nominal thickness
- Weight: 1L-2.2 lbs. (1.0kg); 3L-3.0 lbs. (1.4kg); 7L-4.6 lbs. (2.1kg); 11L-8.2 lbs. (3.9kg); 17L-9.9 lbs. (5.5kg); 23L-12.8 lbs. (7.8kg)

ELECTRICAL SYSTEM
- Input Voltage: 120-277V or 347-480V, 50/60Hz
- Power Factor: > 0.9 at full load
- Total Harmonic Distortion: < 20% at full load
- Integral 10kV surge suppression protection standard.
- When code dictates fusing, a slow blow fuse or type C/D breaker should be used to address inrush current
- Designed with 0-10V dimming capabilities. Controls by others
- 10V Source Current: 0.20 mA
- Operating Temperature Range: -30˚C ~ +40˚C (-22˚F ~ +104˚F)
- Snap connectors make wiring quick and simple

REGULATORY & VOLUNTARY QUALIFICATIONS
- cULus Listed
- Suitable for wet locations
- Designed for downlight applications only
- Meets NEMA CB2.77 standards
- Drivers and LEDs are UL Recognized in accordance with UL8750
- Enclosure meets IP65 requirements per IEC 60529
- Certified to ANSI C136.31-2001, 3G vibration standards
- ANSI C136.2 10kV surge protection, tested in accordance with IEEE/ANSI C62.41.2
- Meets FCC Part 15, Subpart B, Class A standards for conducted and radiated emissions
- Luminaire and finish endurance tested to withstand 5,000 hours of elevated ambient salt fog conditions as defined in ASTM Standard B 117
- Meets Buy American requirements within AIRA
- RoHS compliant. Consult factory for additional details
- Dark Sky Friendly. IDA Approved when ordered with 30K CCT. Please refer to http://darksky.org/our-work/lighting/lighting-for-industry/fsa/fsa-products/ for most current information

CA RESIDENTS WARNING: Cancer and Reproductive Harm – www.p65warnings.ca.gov

WARRANTY
- The NCT series offers a limited 5 year warranty on the luminaire / 1 year on photocell accessory

Lumen Package	Weight	Dim "A"	Dim "B"	Dim "C"	Dim "D"
1L*	2.2 lbs. (1.0kg)	3.7" (93mm)	5.4" (136mm)	8.7" (220mm)	5.6" (141mm)
3L*	3.0 lbs. (1.4kg)	4.6" (192mm)	5.4" (136mm)	8.7" (220mm)	3.9" (100mm)
7L*	4.6 lbs. (2.1 kg)	6.5" (165mm)	5.4" (136mm)	9.8" (250mm)	6.4" (163mm)

Made in the U.S.A. of the U.S. and imported parts.
Meets Buy American requirements for AIRA.

WLS LIGHTING SYSTEMS
6820 Corporation Pkwy
Fort Worth, TX 76126
800.633.8711
www.wlslighting.com

Project Name: _____
Date: _____
Location: _____
Notes: _____

29 REV. 04/21
Specifications subject to change without notice.

NCT SERIES LED WALL

ORDERING INFORMATION SELECT APPROPRIATE CHOICE FROM EACH COLUMN TO FORMULATE ORDER CODE.
Refer to example below.

PRODUCT	VERSION	MOUNTING	OPTIC	LUMEN PACKAGE	COLOR TEMPERATURE	VOLTAGE	COLOR OPTIONS
NCT	A	WM Wall Mount	T3 Type III Medium	**Small** **1L** 1,600 lumens • Not available in 347-480V **3L** 3,500 lumens **7L** 7,000 lumens **Large** **11L** 11,000 lumens **17L** 17,000 lumens **23L** 23,000 lumens	**30K** 3000K **40K** 4000K **50K** 5000K	**UL** Universal 120-277V **UH** Universal 347-480V	**BK** Black **BZ** Bronze **SV** Silver **WH** White
ORDER:							
NCT	A	WM					

Example: WLS-NCT-A-WM-T3-7L-40K-UH-BZ

ELECTRICAL DATA

Lumen Package	System Watts 120-277V	System Watts 347-480V	Total Current (A)					
			120V	208V	240V	277V	347V	480V
1L	12	N/A	0.12	0.07	0.05	0.05	N/A	N/A
3L	24	24	0.24	0.14	0.12	0.10	.008	0.06
7L	46	46	0.46	0.27	0.23	0.20	0.16	0.12
11L	74	74	0.74	0.43	0.37	0.32	0.26	0.19
17L	111	111	1.11	0.64	0.56	0.48	0.38	0.28
23L	148	148	1.48	0.85	0.74	0.64	0.51	0.37

11L - 23L



Lumen Package	Weight	Dim "A"	Dim "B"	Dim "C"
11L	8.2 lbs. (3.9kg)	12.10" (310mm)	5.51" (140mm)	12.36" (314mm)
17L	9.5 lbs. (5.5kg)	16.26" (413mm)	5.51" (140mm)	12.36" (314mm)
23L	12.8 lbs. (7.8 kg)	20.30" (516mm)	5.51" (140mm)	12.36" (314mm)

WLS LIGHTING SYSTEMS
6820 Corporation Pkwy
Fort Worth, TX
76126800.633.8711
www.wlslighting.com

Project Name: _____
Date: _____
Location: _____
Notes: _____

29 REV. 01/21
Specifications subject to change without notice.

NCT SERIES LED WALL

Type II Medium Distribution						
System Watts	3000K			4000K/5000K		
	Initial Delivered Lumens*	Bug Ratings ** Per TM-15-11	Efficacy (LPW)	Initial Delivered Lumens*	Bug Ratings ** Per TM-15-11	Efficacy (LPW)
1L	1,530	B1 U0 G1	128	1,590	B1 U0 G1	132
3L	3,250	B1 U0 G1	135	3,370	B1 U0 G1	140
7L	6,575	B2 U0 G1	143	6,750	B2 U0 G1	147
11L	10,800	B3 U0 G2	146	11,175	B3 U0 G2	151
17L	16,500	B3 U0 G3	149	17,100	B3 U0 G3	154
23L	21,780	B3 U0 G3	147	22,500	B3 U0 G3	153

* Initial delivered lumens at 25° C (77° F). Actual production yield may vary between -10 and +10% of initial delivered lumens.
** For more information on the IES BUG (Backlight - Uplight - Glare) rating visit: https://www.ies.org/wp-content/uploads/ 2017/03/TM-15-11BUGRatingsAddendum.pdf. Valid with no tilt

WLS LIGHTING SYSTEMS
6820 Corporation Pkwy
Fort Worth, TX 76126
800.633.8711
www.wlslighting.com

Project Name: _____
Date: _____
Location: _____
Notes: _____

29 REV. 01/21
Specifications subject to change without notice.

LIGHTING PLAN DEVELOPED BY WLS LIGHTING. PLEASE CONTACT KEN BRONSTAD AT 817-840-9332 (DIRECT), 817-291-9421 (CELL), OR KBRONSTAD@WLSLIGHTING.COM FOR QUESTIONS.

REVISIONS

NO.	DATE	DESCRIPTION
1	-	-
2	-	-
3	-	-
4	-	-
5	-	-
6	-	-

PLAN INFORMATION

PROJECT NO.	NTR21002
FILENAME	NTR21002-CVR+DETAILS
CHECKED BY	LAM
DRAWN BY	AP
SCALE	N/A
DATE	12. 15. 2021

SHEET

LIGHTING DETAILS

L6.02

PRELIMINARY DRAWING - NOT RELEASED FOR CONSTRUCTION

M:\Projects\NTR\NTR21002\04-Production\Engineering\Construction Documents\Current Drawings\NTR21002-CVR+DETAILS.dwg, 12/14/2021 2:44:59 PM, Lauren Micallef